



CADENAS

Description

Synthetic lubricant in aerosol can with excellent adhesiveness for motorcycle chains and other open transmission systems, including those which work at high temperatures, under extreme tension and dirt (dust, sludge, clay, external pollution, etc.).

Qualities

- Excellent load capacity, anti-wear and anti-corrosion agents.
- Exceptional anti-friction property, thereby improving the adherence of the product to the transmission chains and keeping the wheel rim cleaner.
- High friction quotient as it contains micronized teflon.
- Water repellent.
- Does not contain CFC's.

Technical Characteristics

	UNIT	METHOD	VALUE
Colour			Yellow
Copper corrosion, 3h. 100°C		ASTM D 130	1a
Rust distilled water		ASTM D 665	Pasa
4 ball machine, scar diameter 40 Kg. 1200 rpm 75°C 1 h. scar diameter	mm	ASTM D 2266	0,35
4 ball machine, scar diameter 80 Kg. 1 min. scar diameter	mm	DIN 51530	0,37

Available in

Sprays.

Hazard Identification

This product is not classified as toxic or hazardous under current legislation.

Handling

Certain minimum precautions to avoid prolonged contact with the skin should be taken when handling. The use of gloves, visors or masks is recommended in order to avoid splashes.

Health and safety hazards

Inhalation: Minimum risk of inhalation as it is a non-volatile product.

Ingestion: Does not provoke vomiting. Drink water. Seek medical assistance.

Contact with Skin: Wash with abundant water and soap.

Eyes: Wash with abundant water.

General measures: Seek medical assistance.

Fire fighting measures

No special measures are required.

Fire control: Foams, dry chemicals, CO₂, water spray. Do not apply water jet directly as this may cause the product to spread.

Environmental precautions

Danger of physical contamination in the case of spillage (water flows, coastal areas, the ground, etc.) due to its floating capacity and oily consistency which may cause damage to fauna and flora with which it comes into contact. Avoid its penetration into water containers or outlets.

Decontamination and cleaning: Treat as an accidental oil spillage. Avoid spreading by using mechanical barriers and eliminate using both physical and chemical means.

Emergency telephone number. Instituto Nacional de Toxicología 915620420

A safety data file exists.

Unless otherwise specified, the values cited in technical characteristics should be considered as typical.

