



SINTETICO 2T

Description

High quality synthetic oil for use in all 2T engines. It boasts a balanced formula in order to obtain high engine performance and protect the engine against wear and residue formation without increasing smoke emissions.

Meets the JASO requirements in level FB, and those of API TC+.

Qualities

- High lubricant film stability.
- Reduces friction and wear.
- Good thermal and oxidation stability.
- Prevents segment formation and the formation of carbon residues.
- Excellent performance in pre-mix appliances.

Quality Levels

- JASO FB
- API TC+

Technical Characteristics

	UNIT	METHOD	VALUE
Density, 15°C	g/cm ³	ASTM D 4052	0,873
Viscosity, 100°C	cSt	ASTM D 445	8,5
Viscosity, 40°C	cSt	ASTM D 445	45 min.
Viscosity Index	-	ASTM D 2270	140 mín.
Flash Point, COC	°C	ASTM D 92	95 mín.
Pour Point	°C	ASTM D 97	-18
T. B. N.	mg KOH/g	ASTM D 2896	3
Sulphated Ash	% weight	ASTM D 874	0,1

Available in

185 kg drums, 1 and 0,5 litre cans and 125 ml. tubes.

Hazard Identification

This product is not classified as toxic or hazardous under current legislation.

Handling

Certain minimum precautions to avoid prolonged contact with the skin should be taken when handling. The use of gloves, visors or masks is recommended in order to avoid splashes.

Health and safety hazards

Inhalation: Minimum risk of inhalation as it is a non-volatile product.

Ingestion: Does not provoke vomiting. Drink water. Seek medical assistance.

Contact with Skin: Wash with abundant water and soap.

Eyes: Wash with abundant water.

General measures: Seek medical assistance.

Fire fighting measures

No special measures are required.

Fire control: Foams, dry chemicals, CO₂, water spray. Do not apply water jet directly as this may cause the product to spread.

Environmental precautions

Danger of physical contamination in the case of spillage (water flows, coastal areas, the ground, etc.) due to its floating capacity and oily consistency which may cause damage to fauna and flora with which it comes into contact. Avoid its penetration into water containers or outlets.

Decontamination and cleaning: Treat as an accidental oil spillage. Avoid spreading by using mechanical barriers and eliminate using both physical and chemical means.

Emergency telephone number. Instituto Nacional de Toxicología 915620420

A safety data file exists.

Unless otherwise specified, the values cited in technical characteristics should be considered as typical.