



ATF 3

Description

High quality fluid recommended for the automatic transmissions of most vehicles as well as in selected manual transmissions. It can be used whenever a Dexron III G type product is specified and is also suitable as a power steering or hydraulic fluid in certain applications.

This versatile product meets most applications where a friction modified automatic transmission fluid is required and it is suitable for light vehicles and elements of public work machinery: power shift transmissions, torque converters, gearboxes, etc.

Quality level

- DEXRON III G
- Allison C-4
- Ford Mercon
- MB 236.1 & 236.5 (listed)
- ZF TE-ML 02F, 03D, 04D, 11B, 14A, 17C

Technical Data

	UNITS	METHOD	VALUE
Colour		VISUAL	Red
Density @ 15°C	g/cm ³	ASTM D-4052	0.8630
Viscosity @ 100°C	cSt	ASTM D-445	7.65
Viscosity @ 40°C	cSt	ASTM D-445	36
Viscosity @ -40°C	cP	ASTM D-2983	20,000 max.
Viscosity Index		ASTM D-2270	215
Flash Point	°C	ASTM D-92	Min 160
Pour Point	°C	ASTM D-97	Max -42

Packs

- 185 kg drums
- Cases of 12X1 l. plastic packs

Hazard Identification

This product is not classified as toxic or hazardous under current legislation.

Handling

Certain minimum precautions to avoid prolonged contact with the skin should be taken when handling. The use of gloves, visors or masks is recommended in order to avoid spillage.

Health and safety hazards

Inhalation: Minimum risk of inhalation since it is a non-volatile product.

Ingestion: Do not promote vomiting. Drink water. Seek medical assistance.

Contact with Skin: Wash with abundant water and soap.

Eyes: Wash with abundant water.

General measures: Seek medical assistance.

Fire fighting measures

No special measures are required.

Fire control: Foams, dry chemicals, CO₂, water spray. Do not apply water jet directly as this may cause the product to spread.

Environmental precautions

Danger of physical contamination in the case of spillage (water flows, coastal areas, the ground, etc.) due to its floating capacity and oily consistency which may cause damage to fauna and flora with which it comes into contact. Avoid its penetration into water containers or outlets.

Decontamination and cleaning: Treat as an accidental oil spillage. Avoid spreading by using mechanical barriers and eliminate using both physical and chemical means.

**Emergency telephone number. Instituto Nacional de Toxicología
915620420**

A material safety data sheet can be consult if neccesary.

Unless otherwise specified, the values cited in technical characteristics should be considered as typical.