

# PREMIUM TECH R C4 5W-30



AUTOMOTIVE

## Lubricants

### Description

ACEA C4 quality synthetic lubricant oil, specially recommended in vehicles with particle filters and exhaust fume treatment. Stands out for its low ash production (Low SAPS). It is also a long-life lubricant, allowing significant extension of oil change intervals; always according to the manufacturer's recommendations.

### Properties

- Its reduced ash content (Low SAPS) makes it essential for ensuring the durability of new technologies applied to reduce pollutant emission levels, such as diesel particle filters (DPF).
- Contributes to reducing CO<sub>2</sub> emissions, obtaining fuel savings of up to 1 % compared to other lubricants under standard M111FE test conditions.
- Valid for Renault, Dacia, Nissan and Suzuki.

### Quality Levels

- ACEA C4

### Technical specifications

	UNIT	METHOD	VALUE
SAE GRADE			5W-30
Density at 15 °C	g/mL	ASTM D 4052	0.853
Viscosity at 100 °C	cSt	ASTM D 445	12.1
Viscosity at 40 °C	cSt	ASTM D 445	70
Viscosity at -30 °C	cP	ASTM D 5293	6600 max.
Viscosity index	-	ASTM D 2270	171
Flash point, open cup	°C	ASTM D 92	200 min.
Pour point	°C	ASTM D 97	-30
T.B.N.	mg KOH/g	ASTM D 2896	6

A safety data file is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 2. August 2016.