

# CARTAGO TRACCIÓN INTEGRAL EP 75W-90

TRANSMISSIONS AND GEARBOXES



## Lubricants

### Description

Synthetic multigrade lubricant oil, with high thermal stability, recommended for auto-locking transmissions or limited slip differentials (LSD) working under extreme pressure conditions, contact loads and slip characteristic of vehicles used for sports driving.

### Properties

- Great load bearing capacity and capacity to withstand momentarily high temperatures.
- Very good resistance to ageing.
- Excellent antirust and anti-foam properties.
- Good fluidity when cold and very good viscosity at high temperatures.
- Keeps gear assemblies clean thus reducing maintenance costs.
- Specially formulated to efficiently protect contact surfaces from scratches.
- High quality synthetic product which enables the periods between oil changes to be prolonged and also reduces noise in the differential.

### Quality Level

- API GL-5, LSD

### Technical specifications

|                       | UNIT | METHOD      | VALUE       |
|-----------------------|------|-------------|-------------|
| SAE Grade             |      |             | 75W-90      |
| Density at 15 °C      | g/mL | ASTM D 4052 | 0.865       |
| Viscosity at 100 °C   | cSt  | ASTM D 445  | 16.0        |
| Viscosity at 40 °C    | cSt  | ASTM D 445  | 90          |
| Viscosity at -40 °C   | cP   | ASTM D 2983 | 150000 max. |
| Viscosity index       | -    | ASTM D 2270 | 190 min.    |
| Flash point, open cup | °C   | ASTM D 92   | 142 min.    |
| Pour point            | °C   | ASTM D 97   | -42         |
| FZG, Step 12          |      | DIN 51354   | Pass        |

*The above mentioned characteristics are typical values and should not be considered product specifications.*

A safety information file is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 3. March 2018