

DIESEL MULTITURBO 25W50



AUTOMOTIVE

Lubricants

Description

Multigrade lubricant oil for heavy, natural aspiration or turbocharged diesel engines where an API CF quality standard is required. Its viscosity enables it to be used in operating conditions with high ambient temperatures.

Properties

- Guarantees good lubrication in normal service conditions.
- Prevents the formation of lacquers and varnishes thanks to its dispersant additives.
- Its detergent capacity keeps combustion residue under control, thus preventing it from being deposited in the engine.
- Its viscosity allows it to be used in warm atmospheres.
- It maintains an adequate pressure and temperature under all service conditions.

Quality Level

- API SF/CF

Technical specifications

	UNIT	METHOD	VALUE
SAE GRADE			25W50
Density at 15 °C	g/cm ³	ASTM D 4052	0.902
Viscosity at 100 °C	cSt	ASTM D 445	19.2
Viscosity at 40 °C	cSt	ASTM D 445	211
Viscosity at -10 °C	cP	ASTM D 5293	13000 max.
Viscosity index	-	ASTM D 2270	95 min.
Flash point, open point	°C	ASTM D 92	230 min.
Pour point	°C	ASTM D 97	-12
T. B. N.	mg KOH/g	ASTM D 2896	11.1
Bosch Injector Shearing: Viscosity at 100 °C after shearing	cSt	CEC-L014-93	18.48
Noack Volatility, 1hr at 250 °C	% in weight	CEC-L-40-93	2.9
HTHS, viscosity at 150 °C	cP	CEC-L-36-A-90	>3.7

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 2. September 2013.