

# GAS LOW ASH 15W40

AUTOMOTIVE

Lubricants



## Description

Mineral lubricating oil recommended for use in DEUTZ and DETROIT DIESEL vehicles or stationary engines that operate with compressed natural gas (CNG) or with propane and butane (LPG), and which require a limited ash content.

## Properties

- Limited ash content to prevent the formation of residues on spark plugs that can cause noise and preignition.
- Wear testing on the valve trains for CUMMINS engines show excellent performance. The wear is below the manufacturer's limit and far below that of competing oils.
- The stability of its detergent additives allow for longer change periods, minimising the acidic compounds typical of these types of engines.
- High resistance to corrosion, far above the requirements of the CUMMINS CES 20074 standard.
- The tests conducted in CNG vehicle fleets have shown higher pressure stability at any temperature and in all working conditions.

## Quality Levels

- CUMMINS CES 20074
- API CF
- DETROIT DIESEL DDC 93K216

## Technical specifications

	UNIT	METHOD	VALUE
SAE GRADE			15W40
Density at 15 °C	g/mL	ASTM D 4052	0.884
Viscosity at 100 °C	cSt	ASTM D 445	14.3
Viscosity at 40 °C	cSt	ASTM D 445	109
Viscosity at -20 °C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	135
Flash point, open cup	°C	ASTM D 92	236
Pour point	°C	ASTM D 97	-27
T. B. N.	mg KOH/g	ASTM D 2896	5
Sulphated ashes	% in weight	ASTM D 874	0.6 max.
Bosch Injector Shearing: Viscosity at 100 °C after shear	cSt	CEC L-14-93	12.5
Noack volatility 1hr at 250 °C	% in weight	CEC L-40-93	9.5

A safety information file is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 2. March 2012.