

Description

Monograde lubricant oil for manual gearboxes that require quality level API GL-4. Available in different viscosities according to manufacturers' recommendations and temperature at the time of starting the vehicle.

Properties

- Protects gears against moisture, preventing corrosion and increasing transmission life.
- Excellent compatibility with bronze and copper elements of gearbox synchronisers, allowing for smoother gear changes.
- Prevents foam formation, maintaining constant lubrication of all components and preventing the fatigue wear characteristic of gears.
- Approved by most industrial vehicle manufacturers.

Quality levels, approvals and recommendations

- API GL-4
- MB 235.1*
- ZF TE-ML 08/17A*
- DAF Transmissions
- RENAULT Transmissions
- VW 726
- IVECO 18-1807 MGS2

*Formal approval

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			80W
Density at 15 °C	g/cm3	ASTM D 4052	0,891
Viscosity at 100 °C	cSt	ASTM D 445	11,0
Viscosity at 40 °C	cSt	ASTM D 445	98
Viscosity index	-	ASTM D 2270	< 95
Flash point, open cup	°C	ASTM D 92	190
Pour point	°C	ASTM D 97	-24

The above mentioned characteristics are typical values and should not be considered product specifications.