

RIDER HIGH MILEAGE 4T 25W-50**MOTO**

Description

REPSOL MOTO HIGH MILEAGE 4T 25W-50 is a highly refined lubricant oil designed for four-stroke motorcycles. It is especially recommended for motorcycle taxis that work in warm climates and need API SL quality or below.

Properties

- The high 25W-50 viscosity provides more sealing power for the pistons, improving compression.
- High grade protection for the engine and the gearbox.
- Good detergent-dispersant power to ensure complete engine cleaning.
- Suitable pressure and temperature under all service conditions.

Quality levels, approvals and recommendations

- API SL
- JASO T903:2016 MA2*
- *Formal approval

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			25W-50
Density at 15 °C	g/mL	ASTM D 4052	0,895
Viscosity at 100 °C	cSt	ASTM D 445	18
Viscosity at 40 °C	cSt	ASTM D 445	186
Viscosity at -10 °C	cP	ASTM D 5293	13000 maximum
Viscosity index	-	ASTM D 2270	103
Flash point, open cup	°C	ASTM D 92	245
Pour point	°C	ASTM D 97	-18
T.B.N.	mg KOH/g	ASTM D 2896	6

The above mentioned characteristics are typical values and should not be considered product specifications.