

MOTO HIGH MILEAGE 4T 25W-50

MOTORCYCLE



Lubricants

Description

REPSOL MOTO HIGH MILEAGE 4T 25W-50 is a highly refined lubricant oil designed for four-stroke motorcycles. It is especially recommended for motorcycle taxis that work in warm climates and need API SL quality or below.

Properties

- The high 25W-50 viscosity provides more sealing power for the pistons, improving compression.
- High grade protection for the engine and the gearbox.
- Good detergent-dispersant power to ensure complete engine cleaning.
- Suitable pressure and temperature under all service conditions.

Quality levels

- API SL
- JASO MA2

Technical specifications

	UNIT	METHOD	VALUE
SAE grade			25W-50
Density at 15 °C	g/ml	ASTM D4052	0.895
Viscosity at 100 °C	cSt	ASTM D445	18
Viscosity at 40 °C	cSt	ASTM D445	186
Viscosity at -10 °C	cP	ASTM D5293	13,000 max
Viscosity index	-	ASTM D2270	103
Flash point, open cup	°C	ASTM D92	245
Pour point	°C	ASTM D97	-9
TBN	mg KOH/g	ASTM D2896	7,4

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety data sheet is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 1. June 2017