

MOTO HIGH MILEAGE 4T 25W60

MOTORCYCLE



Lubricants

Description

REPSOL MOTO HIGH MILEAGE 4T 25W60 is a mineral-based lubricant for four-stroke motorcycle engines. It is especially recommended for long-distance motorcycle taxis that need API SG quality or below.

Properties

- Its high 25W60 viscosity gives it more sealing power for the pistons, improving compression.
- High grade protection for the engine and the gearbox.
- Good detergent-dispersant power to ensure complete engine cleaning.
- Suitable pressure and temperature under all service conditions.

Quality levels

- API SG

Technical specifications

	UNIT	METHOD	VALUE
SAE grade			25W60
Density at 15 °C	g/ml	ASTM D4052	0.895
Viscosity at 100 °C	cSt	ASTM D445	24
Viscosity at 40 °C	cSt	ASTM D445	250
Viscosity at -10 °C	cP	ASTM D5293	13,000 max
Viscosity index	-	ASTM D2270	120
Flash point, open cup	°C	ASTM D92	250
Pour point	°C	ASTM D97	-18
TBN	mg KOH/g	ASTM D2896	6.5
Sulphated ashes	% in weight	ASTM D874	0.8
Bosch injector shearing:			
Viscosity at 100 °C after shear	cSt	CEC-L014-93	21.9 min.

A safety data sheet is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 1. February 2015.