

# MOTO MATIC SINTETICO MB 4T 10W-30

MOTO

Lubricantes



## Description

Ultra-high-quality engine oil for high performance 4T engines with fuel saving properties. It contains special additives that improve lubricity and friction control. These additives bring it in line with the JASO MB quality standard. It is recommended for use in motorcycles that require a low-friction lubricant.

JASO MB is recommended especially for dry-clutch scooters and automatic-transmission motorcycles.

## Properties

- It was developed in accordance with the strictest requirements to contribute to fuel savings and consequently to protecting the environment by reducing CO<sub>2</sub> emissions.
- The trials in four-stroke motorcycles under extreme working conditions have confirmed excellent protection against wear.
- Its formula offers a high level of performance and, in turn, guarantees adequate friction reduction for the parts coated in the oil.
- It should only be used when this SAE 10W-30 viscosity level is recommended by the manufacturer of the motorcycle.

## Quality levels

- API SN
- JASO T 903:2016 MB

## Technical specifications

	UNIT	METHOD	VALUE
SAE grade			10W-30
Density at 15 °C	g/cm <sup>3</sup>	ASTM D4052	0.853
Viscosity at 100 °C	cSt	ASTM D445	10.5
Viscosity at 40 °C	cSt	ASTM D445	63
Viscosity at -25 °C	cP	ASTM D5293	7000 max.
Viscosity index	-	ASTM D2270	147
Flash point, open cup	°C	ASTM D92	242
Freezing point	°C	ASTM D97	-42
TBN	mg KOH/g	ASTM D2896	8.7
Sulphated ash	% in weight	ASTM D874	0.73
Bosch injector shear at 100 °C	cSt	ASTM D3945	9.3 min.
Noack volatility at 250 °C	%	DIN 51581	6.3

A safety data sheet is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 2. April 2018.