

# MOTO SCOOTER 2T



MOTORCYCLE

## Lubricants

### Description

It is the ideal synthetic lubricant oil for 2-stroke engine scooters since it has been designed for continual stop-start use, which is so typical of this type of motorcycle. It provides excellent protection against wear and it minimises the emission of contaminating fumes. Furthermore, it supports high engine temperatures in an exemplary way and prevents the formation of carbon deposit in the pistons and the degradation of the exhaust systems. It is suitable for both premix and injector lubrication engines.

### Properties

- Reduces exhaust emissions due to its “smokeless” technology.
- Minimises engine noise.
- Good thermal stability and antioxidant capacity.
- Increases the smoothness and power of the engine.
- Increased protection against wear.

### Quality Levels

- JASO M345 FD (Code 034RYL003)
- API TC
- Aprilia DFI
- ISO-L-EGD
- TISI

### Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0.870
Viscosity at 100 °C	cSt	ASTM D 445	9.6
Viscosity at 40 °C	cSt	ASTM D 445	64
Viscosity INDEX	-	ASTM D 2270	130
Flash point, open cup	°C	ASTM D 92	115
Pour point	°C	ASTM D 97	-33
T. B. N.	mg KOH/g	ASTM D 2896	2
Sulphated ashes	% in weight	ASTM D 874	0.1

A safety information file is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 2. October 2010