

MOTO SINTETICO 2T



MOTORCYCLE

Lubricants

Description

It is essentially suitable for high performance small cylinder capacity 2-stroke engines. Its formulation protects the engine against the formation of deposits in the exhaust and the degradation of engine components. It is suitable for both premix and for injector lubrication system engines. It is perfectly suitable for all types of 2-stroke motorcycles in their very varied disciplines.

Properties

- Highly stable lubricant film.
- Reduces friction and wear.
- Good thermal and oxidative stability.
- Prevents the spark plugs sweating, the pistons from sticking, and the formation of carbonous residues.

Quality Levels

- JASO M345 FD (Code 034RYL004)
- API TC
- Aprilia DFI
- ISO-L-EGD
- TISI

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm ³	ASTM D 4052	0.870
Viscosity at 100 °C	cSt	ASTM D 445	10.0
Viscosity at 40 °C	cSt	ASTM D 445	68
Viscosity index	-	ASTM D 2270	130
Flash point, open cup	°C	ASTM D 92	116
Pour point	°C	ASTM D 97	-33
T. B. N.	mg KOH/g	ASTM D 2896	2
Sulphated ashes	% in weight	ASTM D 874	0.1

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 2. October 2010