

MOTO TRANSMISSION 80W-90

MOTORCYCLE

Lubricants



Description

Lubricant oil formulated for lubricating motorcycle gearboxes. It provides excellent resistance to shearing and ensures that oil bath clutches operate with perfect slipping control in extreme conditions. It prolongs the life of all gearbox components, reduces mechanical noise and helps cold starts.

Properties

- Excellent load-carrying capacity and antiwear.
- Protects and prolongs the life of gearboxes, gears and auxiliary systems.
- Maximum protection against wear and extreme conditions for all parts of the gearbox.
- Compatible with the materials used in the transmissions of all types of motorcycle.

Quality level

- API GL-4

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm ³	ASTM D 4052	0.897
Density at 100 °C	cSt	ASTM D 445	14
Viscosity at 40 °C	cSt	ASTM D 445	137
Viscosity at -26 °C	cP	ASTM D 2983	150000 max.
Viscosity index	-	ASTM D 2270	99
Flash point, open cup	°C	ASTM D 92	230
Pour point	°C	ASTM D 97	-33
FZG, Step 12	-	ASTM D 51354	Pass

The aforementioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 3. September 2019.