

TALUSIA HR 70



LUBMARINE

Lubricants

Description

Marine lubricants with very high safety margins, specially formulated for lubricating 2-stroke crosshead low-speed diesel engine cylinders.

Developed in close collaboration with OEMs, it is the most widely-used lubricant in engines that run on medium or heavy fuel with a high sulphur content.

Its high acid neutralisation capacity ensures excellent cylinder protection against corrosion and wear, allowing extending the length of time between engine overhauls.

Properties

- Minimal wear of the sleeve and piston rings.
- Maximum cleaning.
- Reduces engine maintenance costs.
- Longer time between services.

Quality levels, approvals and recommendations

- The lubricant TALUSIA HR complies with the requirements and recommendations of the leading 2-strokes engine manufacturers (MAN Diesel & Turbo y Wärtsilä.). Its effectiveness has been proven in thousands of engines of all kinds, running under all conditions.

Technical specifications

	UNIT	METHOD	VALUE
SAE grade			50
Density at 15 °C	g/cm ³	ASTM D 4052	0.940
Viscosity at 100 °C	cSt	ASTM D 445	19.5
Flash point, open cup	°C	ASTM D 92	230 min.
Pour point	°C	ASTM D 97	-9
TBN	mg KOH/g	ASTM D 2896	70

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety data sheet is available on request.

repsol.com
+34 901 111 999
lubricantes@repsol.com

Technical data sheet for Lubricants. Revision 5. July 2020.