

# TALUSIA LS 25



LUBMARINE

Lubricants

## Description

Marine lubricant specially formulated for lubricating 2-stroke crosshead low-speed diesel engine cylinders.

Allowing for the most stringent conditions encountered in service, TALUSIA LS 25 covers the special operational needs of the slow speed 2-stroke engines running on distillate fuels with up to 0.1% sulphur content (ULSFO).

Its optimized formulation provides excellent cleanliness and outstanding deposit control.

## Properties

- Minimal wear of the sleeve and piston rings.
- Maximum cleaning.
- Low alkalinity.
- Reduces engine maintenance costs.
- Excellent grime control due to its low ash chemistry.

## Quality levels, approvals and recommendations

- TALUSIA LS 25 lubricant is approved by the main manufacturers of 2-stroke engines, MAN Diesel & Turbo and Wärtsilä.

## Technical specifications

	UNIT	METHOD	VALUE
SAE grade			50
Density at 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0.910
Viscosity at 100 °C	cSt	ASTM D 445	19.0
Flash point, open cup	°C	ASTM D 92	230 min.
Pour point	°C	ASTM D 97	-10
TBN	mg KOH/g	ASTM D 2896	25

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety data sheet is available on request.

repsol.com  
+34 901 111 999  
[lubricantes@repsol.com](mailto:lubricantes@repsol.com)

Technical data sheet for Lubricants. Revision 2. July 2020.