

TALUSIA UNIVERSAL

LUBMARINE

Lubricants



Description

Marine lubricant with a patented formula specially designed for the lubrication of cylinders of 2-stroke low-speed diesel engines that run on a wide range of fuels with a sulphur content from 0.0% to 1.5%.

The unique composition of TALUSIA UNIVERSAL endows it with exceptional capacity to neutralise acids during combustion.

Designed for the most severe working conditions, TALUSIA UNIVERSAL is suitable for special working conditions using fuels with a sulphur content of between 0.5% and 3.5%.

TALUSIA UNIVERSAL is a premium solution for the lubrication of all modern diesel and dual-fuel two-stroke engines using IMO 2020 and ECA compliant fuels.

Properties

- Minimum wear of the piston liner and rings with maximum cleanliness.
- Reduces engine maintenance costs, extending the time between revisions.

Quality levels, approvals and recommendations

- MAN B&W 2-stroke diesel.
- Wärtsilä-Sulzer 2-stroke diesel.
- Japan Engine (UE Engines).

Technical specifications

| | UNIT | METHOD | VALUE |
|-----------------------|-------------------|-------------|----------|
| SAE grade | | | 50 |
| Density at 15 °C | g/cm ³ | ASTM D 4052 | 0.930 |
| Viscosity at 100 °C | cSt | ASTM D 445 | 19.0 |
| Flash point, open cup | °C | ASTM D 92 | 230 min. |
| Pour point | °C | ASTM D 97 | -9 |
| TBN | mg KOH/g | ASTM D 2896 | 57 |

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety data sheet is available on request.

repsol.com
+34 901 111 999
lubricantes@repsol.com

Technical data sheet for Lubricants. Revision 5. July 2020.