



RIDER HIGH MILEAGE 4T 25W-60

Description

RIDER HIGH MILEAGE 4T 25W-60 is a mineral-based lubricant for four-stroke motorcycle engines. It is especially recommended for long-distance motorcycle taxis that need API SG quality or below.

Properties

- Its high 25W-60 viscosity gives it more sealing power for the pistons, improving compression.
- High grade protection for the engine and the gearbox.
- Good detergent-dispersant power to ensure complete engine cleaning.
- Suitable pressure and temperature under all service conditions.

Quality levels, approvals and recommendations

• JASO T 903:2016 MA2*

• API: SG

*Formal approval

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			25W-60
Density at 15 °C	g/mL	ASTM D4052	0.893
Viscosity at 100 °C	cSt	ASTM D445	24
Viscosity at 40 °C	cSt	ASTM D445	250
Viscosity at -10 °C	cP	ASTM D5293	<13,000
Viscosity index	-	ASTM D2270	120
Flash point, open cup	°C	ASTM D92	250
Pour point	°C	ASTM D97	-18
TBN	mg KOH/g	ASTM D2896	6.5
Sulphated ashes	% in weight	ASTM D874	0.8
Bosch Injector Shearing: Viscosity at 100 °C	cSt	CEC L-14-93	>21.9

The above mentioned characteristics are typical values and should not be considered product specifications.