

HG 40 & 50



AUTOMOTIVE

Lubricants

Description

Monograde lubricant oil developed to cover the needs of low demand 4-stroke petrol engines. Its detergent capacity keeps combustion waste under control, thereby preventing it from being deposited in the engine. As it is made with refined mineral base oils, its carefully studied additives enable oxidation, corrosion and wear of internal engine parts to be controlled.

Properties

- Oil with anti-wear properties.
- Good anti-corrosion properties
- Low consumption and stable against oxidation thanks to the use of refined and low volatility base oils.

Quality Level

- API SB

Technical specifications

	UNIT	METHOD	VALUE	
SAE Grade			40	50
Density at 15 °C	g/mL	ASTM D 4052	0.892	0.897
Viscosity at 100 °C	cSt	ASTM D 445	14.9	19.1
Viscosity at 40 °C	cSt	ASTM D 445	154	225
Viscosity index	-	ASTM D 2270	95 min.	95 min.
Flash point	°C	ASTM D 92	220 min.	230 min.
Pour point	°C	ASTM D 97	-21	-18
Sulphated ashes	% in weight	ASTM D 874	0.1	0.1

A safety data file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 1 April 2016.