

Description

High-performance mineral lubricant that is suitable for a wide variety of two-stroke engines. This engine oil is the perfect choice for gardening and forestry applications such as chainsaws and lawnmowers. The Mix 2T is a clean oil that takes care of the engine, protects all metallic pieces from wear and corrosion and offers optimal lubrication for the combustion chamber.

Properties

- High lubricating power, reducing wear and extending the engine's life.
- Minimizes the formation of deposits, keeping exhaust ports clean.
- Reduces spark plug fouling and prevents piston rings from sticking.

Quality levels, approvals and recommendations

- API TC
- JASO M 345 FB

* Formal approval

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/ml	ASTM D 4052	0.880
Colour			Red
Viscosity at 100 °C	cSt	ASTM D445	8.9
Viscosity at 40 °C	cSt	ASTM D445	65
Viscosity index	-	ASTM D 2270	110
Flash point (COC)	°C	ASTM D 92	146
TBN	mg KOH/g	ASTM D 2896	1.6
Pour point	°C	ASTM D 97	-12

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety data sheet is available upon request.

repsol.com
+34 901 111 999
lubricantes@repsol.com

Edition 1, June 2020

Technical data sheet for Lubricants.