

ANTICONGELANTE REFRIGERANTE MAXIMUM QUALITY PURO

(MAXIMUM QUALITY PURE COOLANT
ANTIFREEZE)



Car care

Description

Antifreeze formulated from ethylene glycol and anticorrosive and anti-foam additives. It is free of amines, nitrites and phosphates. Recommended for all types of cooling circuits in diesel and petrol engines, and especially for aluminium and aluminium alloy circuits. Mixed with water in the range 30-50% it provides excellent antifreeze and cooling properties and very good protection from metal surfaces.

Properties

- Excellent protection against corrosion and cavitation, even at low concentrations.
- Mixable with water in any proportion-
- Prevents foam formation.
- Hinders the formation of deposits and sludge in the cooling circuit.
- Great thermal stability.
- It possesses alkaline capacity to neutralise the acid combustion gases which inevitably leak into the cooling circuit.
- Compatible with joints and seals, thus preventing fluid loss risks.

Quality levels

- ASTM D 3306
- BS 6580:1992
- MAN 324 Type NF
- MB 325.0
- VW TL774 C
- BMW GS 94000

Technical specifications

| | UNIT | METHOD | VALUE |
|-------------------------|-------------------|-------------|-------|
| Appearance | | Visual | Blue |
| pH | - | ASTM D 1287 | 7,2 |
| Density at 20 °C | g/cm ³ | DIN 51757-4 | 1,122 |
| Freezing point (at 50%) | ° C | ASTM D 1177 | -40 |
| Boiling point | ° C | ASTM D 1120 | >165 |
| Reserve alkalinity | ml HCl 0.1N | ASTM D 1121 | 16 |

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

www.repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 7. November 2017.