

Description

Universal Tractor Transmission Oil (UTTO) suitable for lubricating agricultural and construction transmissions, clutches, and wet brakes. Its viscosity and additives make it appropriate for use in hydraulic systems and power take-offs, where a multigrade fluid with dispersant capacity is required.

TERRA UTTO can be used in gearboxes and differentials where a GL-4 performance level is required.

Properties

- Recommended for equipment where a common oil sump is used for the transmission, differential, final drive, wet brake, wet clutch and hydraulic components.
- Viscosity grade SAE J306: 75W-80.
- Equivalent to 10W-30 according SAE J300. Not to be used as engine oil.
- Provides wear protection and, at the same time, it reduces noise and shudder in wet brake systems.
- High Excellent thermal and oxidation stability.
- Extends clutch, elastomers and seals service life.

Quality levels

- UTTO, Universal Tractor Transmission Oil
- API GL-4
- SAE 75W-80

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/mL	ASTM D 4052	0.879
Viscosity at 100 °C	cSt	ASTM D 445	10.0
Viscosity at 40 °C	cSt	ASTM D 445	62
Viscosity index	-	ASTM D 2270	140 min.
Flash point, open cup	°C	ASTM D 92	180 min.
Pour point	°C	ASTM D 97	-42

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 1. May 2017.